


INSERTOS

Tipo H
(Ferro Fundido)



Referência para Pedido	Estoque DP5010	Dimensões (mm)			Suporte Correspondente
		D1	L2	S1	
TAWKH1400TG	▲	14.0	7.1	5.0	TAWSNH 1400S16
1410TG	▲	14.1	7.1	5.0	TAWMNH 1400S16
1420TG	▲	14.2	7.1	5.0	TAWLNH 1400S16
1430TG	▲	14.3	7.1	5.0	
1440TG	▲	14.4	7.1	5.0	
1450TG	▲	14.5	7.0	5.0	
1460TG	▲	14.6	7.0	5.0	
1470TG	▲	14.7	7.0	5.0	TAWSNH 1500S20
1480TG	▲	14.8	7.0	5.0	
1490TG	▲	14.9	7.0	5.0	TAWMNH 1500S20
1500TG	▲	15.0	6.9	5.0	
1510TG	▲	15.1	6.9	5.0	TAWLNH 1500S20
1520TG	▲	15.2	6.9	5.0	
1530TG	▲	15.3	6.9	5.0	
1540TG	▲	15.4	6.9	5.0	
1550TG	▲	15.5	7.3	6.0	
1560TG	▲	15.6	7.3	6.0	
1570TG	▲	15.7	7.3	6.0	TAWSN 1600S20
1580TG	▲	15.8	7.3	6.0	
1590TG	▲	15.9	7.3	6.0	TAWMN 1600S20
1600TG	▲	16.0	7.2	6.0	
1610TG	▲	16.1	7.2	6.0	TAWLN 1600S20
1620TG	▲	16.2	7.2	6.0	
1630TG	▲	16.3	7.2	6.0	
1640TG	▲	16.4	7.2	6.0	
1650TG	▲	16.5	7.1	6.0	
1660TG	▲	16.6	7.1	6.0	
1670TG	▲	16.7	7.1	6.0	TAWSN 1700S20
1680TG	▲	16.8	7.1	6.0	
1690TG	▲	16.9	7.1	6.0	TAWMN 1700S20
1700TG	▲	17.0	7.0	6.0	
1710TG	▲	17.1	7.0	6.0	TAWLN 1700S20
1720TG	▲	17.2	7.0	6.0	
1730TG	▲	17.3	7.0	6.0	
1740TG	▲	17.4	7.0	6.0	
1750TG	▲	17.5	6.8	6.0	
1760TG	▲	17.6	6.8	6.0	
1770TG	▲	17.7	6.8	6.0	TAWSN 1800S20
1780TG	▲	17.8	6.8	6.0	
1790TG	▲	17.9	6.8	6.0	TAWMN 1800S20
1800TG	▲	18.0	6.8	6.0	
1810TG	▲	18.1	6.8	6.0	TAWLN 1800S20
1820TG	▲	18.2	6.8	6.0	
1830TG	▲	18.3	6.8	6.0	
1840TG	▲	18.4	6.8	6.0	

Referência para Pedido	Estoque DP5010	Dimensões (mm)			Suporte Correspondente
		D1	L2	S1	
TAWKH1850TG	●	18.5	8.6	7.0	
1860TG	●	18.6	8.6	7.0	
1870TG	●	18.7	8.6	7.0	TAWSN 1900S25
1880TG	●	18.8	8.6	7.0	
1890TG	●	18.9	8.6	7.0	TAWMN 1900S25
1900TG	●	19.0	8.5	7.0	
1910TG	●	19.1	8.5	7.0	TAWLN 1900S25
1920TG	●	19.2	8.5	7.0	
1930TG	●	19.3	8.5	7.0	
1940TG	●	19.4	8.5	7.0	
1950TG	●	19.5	8.4	7.0	
1960TG	●	19.6	8.4	7.0	
1970TG	●	19.7	8.4	7.0	TAWSN 2000S25
1980TG	●	19.8	8.4	7.0	
1990TG	●	19.9	8.4	7.0	TAWMN 2000S25
2000TG	●	20.0	8.3	7.0	
2010TG	□	20.1	8.3	7.0	TAWLN 2000S25
2020TG	□	20.2	8.3	7.0	
2030TG	□	20.3	8.3	7.0	
2040TG	□	20.4	8.3	7.0	
2050TG	●	20.5	8.2	7.0	
2060TG	□	20.6	8.2	7.0	
2070TG	□	20.7	8.2	7.0	TAWSN 2100S25
2080TG	□	20.8	8.2	7.0	
2090TG	□	20.9	8.2	7.0	TAWMN 2100S25
2100TG	●	21.0	8.1	7.0	
2110TG	□	21.1	8.1	7.0	TAWLN 2100S25
2120TG	□	21.2	8.1	7.0	
2130TG	□	21.3	8.1	7.0	
2140TG	□	21.4	8.1	7.0	
2150TG	●	21.5	9.8	8.0	
2160TG	□	21.6	9.8	8.0	
2170TG	□	21.7	9.8	8.0	TAWSN 2200S25
2180TG	□	21.8	9.8	8.0	
2190TG	□	21.9	9.8	8.0	TAWMN 2200S25
2200TG	●	22.0	9.7	8.0	
2210TG	□	22.1	9.7	8.0	TAWLN 2200S25
2220TG	□	22.2	9.7	8.0	
2230TG	□	22.3	9.7	8.0	
2240TG	□	22.4	9.7	8.0	
2250TG	●	22.5	9.6	8.0	TAWSN 2300S25
2260TG	□	22.6	9.6	8.0	
2270TG	□	22.7	9.6	8.0	TAWMN 2300S25
2280TG	□	22.8	9.6	8.0	
2290TG	□	22.9	9.6	8.0	TAWLN 2300S25

FURAÇÃO

Referência para Pedido	Estoque	Dimensões (mm)			Suporte Correspondente
	DP5010	D1	L2	S1	
TAWKH2300TG	●	23.0	9.5	8.0	TAWSN 2300S25
2310TG	□	23.1	9.5	8.0	TAWMN 2300S25
2320TG	□	23.2	9.5	8.0	TAWLN 2300S25
2330TG	□	23.3	9.5	8.0	
2340TG	□	23.4	9.5	8.0	
2350TG	●	23.5	9.4	8.0	
2360TG	□	23.6	9.4	8.0	
2370TG	□	23.7	9.4	8.0	TAWSN 2400S32
2380TG	□	23.8	9.4	8.0	TAWMN 2400S32
2390TG	□	23.9	9.4	8.0	TAWLN 2400S32
2400TG	●	24.0	9.3	8.0	
2410TG	□	24.1	9.3	8.0	
2420TG	□	24.2	9.3	8.0	
2430TG	□	24.3	9.3	8.0	
2440TG	□	24.4	9.3	8.0	
2450TG	●	24.5	10.8	9.0	
2460TG	□	24.6	10.8	9.0	
2470TG	□	24.7	10.8	9.0	TAWSN 2500S32
2480TG	□	24.8	10.8	9.0	TAWMN 2500S32
2490TG	□	24.9	10.8	9.0	TAWLN 2500S32
2500TG	●	25.0	10.7	9.0	
2510TG	□	25.1	10.7	9.0	
2520TG	□	25.2	10.7	9.0	
2530TG	□	25.3	10.7	9.0	
2540TG	□	25.4	10.7	9.0	
2550TG	●	25.5	10.6	9.0	
2560TG	□	25.6	10.6	9.0	
2570TG	□	25.7	10.6	9.0	TAWSN 2600S32
2580TG	□	25.8	10.6	9.0	TAWMN 2600S32
2590TG	□	25.9	10.6	9.0	TAWLN 2600S32
2600TG	●	26.0	10.5	9.0	
2610TG	□	26.1	10.5	9.0	
2620TG	□	26.2	10.5	9.0	
2630TG	□	26.3	10.5	9.0	
2640TG	□	26.4	10.5	9.0	
2650TG	●	26.5	10.4	9.0	
2660TG	□	26.6	10.4	9.0	
2670TG	□	26.7	10.4	9.0	TAWSN 2700S32
2680TG	□	26.8	10.4	9.0	TAWMN 2700S32
2690TG	□	26.9	10.4	9.0	TAWLN 2700S32
2700TG	●	27.0	10.3	9.0	
2710TG	□	27.1	10.3	9.0	
2720TG	□	27.2	10.3	9.0	
2730TG	□	27.3	10.3	9.0	
2740TG	□	27.4	10.3	9.0	

Referência para Pedido	Estoque	Dimensões (mm)			Suporte Correspondente
	DP5010	D1	L2	S1	
TAWKH2750TG	●	27.5	11.3	10.0	
2760TG	□	27.6	11.3	10.0	TAWSN 2800S32
2770TG	□	27.7	11.3	10.0	TAWMN 2800S32
2780TG	□	27.8	11.3	10.0	TAWLN 2800S32
2790TG	□	27.9	11.3	10.0	
2800TG	●	28.0	11.2	10.0	
2810TG	□	28.1	11.2	10.0	
2820TG	□	28.2	11.2	10.0	
2830TG	□	28.3	11.2	10.0	
2840TG	□	28.4	11.2	10.0	
2850TG	●	28.5	11.1	10.0	
2860TG	□	28.6	11.1	10.0	
2870TG	□	28.7	11.1	10.0	TAWSN 2900S32
2880TG	□	28.8	11.1	10.0	TAWMN 2900S32
2890TG	□	28.9	11.1	10.0	TAWLN 2900S32
2900TG	●	29.0	11.0	10.0	
2910TG	□	29.1	11.0	10.0	
2920TG	□	29.2	11.0	10.0	
2930TG	□	29.3	11.0	10.0	
2940TG	□	29.4	11.0	10.0	
2950TG	●	29.5	10.9	10.0	
2960TG	□	29.6	10.9	10.0	
2970TG	□	29.7	10.9	10.0	TAWSN 3000S32
2980TG	□	29.8	10.9	10.0	TAWMN 3000S32
2990TG	□	29.9	10.9	10.0	TAWLN 3000S32
3000TG	●	30.0	10.8	10.0	
3010TG	□	30.1	10.8	10.0	
3020TG	□	30.2	10.8	10.0	
3030TG	□	30.3	10.8	10.0	
3040TG	□	30.4	10.8	10.0	

● : Estoque mantido. □ : Sem estoque, produzido somente por pedido.

▲ : Estoque mantido. Será substituído por novos produtos.

(Nota: 1 inserto por embalagem)